

SPECIFICATION(规格书)

SPC NO. (规格书编号): 18AWG 特软硅胶线		EVRSION(版本): 1	CUTOF WIRE(截面图) 
DESCRIPTION(产品描述): 18AWG特软硅胶线			
SIZE(规格): 18AWG OD:2.3mm			
REFERENCE(参考): UL758 UL1581			
RATING VOLTAGE(电压)V:	3000		
RATING TEMPERATURE(温度)℃:	-60 -200		
CONSTRUCTION(线材结构):			
CONDUCTOR 导体	AWG(线规)	18AWG	
	CONSTRUCTION(结构)	150/0.08TS+/-0.005mm	
	MATERIAL(材质)	Stranded tinned copper conductor(绞合镀锡铜线)	
	DIA(线径)	1.13mm	
INSULATION(1) 绝缘	MATERIAL(材质)	硅胶	
	AVERAGE THICKNESS(平均厚度)	0.585mm	
	MINIMUM THICKNESS(最薄厚度)	0.5mm	
	DIA(线径)	2.3mm+/-0.1mm	
	COLOR(颜色)	Request according to the customer(根据客户要求)	
INSULATION(2) 绝缘	MATERIAL(材质)		
	AVERAGE THICKNESS(平均厚度)		
	MINIMUM THICKNESS(最薄厚度)		
	DIA(线径)		
	COLOR(颜色)		
MARKING(印字): 18AWG 200℃			
PHYSICAL & ELECTRICAL PROPERTIES(机械物理与电气性能)			
CONDUCTOR RESISTANCE(导体电阻) ohms/km:		23.3Ω/KM	
INSULATION RESISTANCE(承受电流A):		7.5A	
VOLTAGE WITHSTAND TEST(耐电压)kv/min:		3.0KV	
PREPARED(制作): 刘长风	CHECKED(审核): 汪洋	ISSUE DATE(时间): 2018.8.10	