

SPECIFICATION(规格书)

SPC NO. (规格书编号): 6AWG 特软硅胶线		EVRSION(版本): 1	CUTOF WIRE(截面图) 
DESCRIPTION(产品描述): 6AWG特软硅胶线			
SIZE(规格): 6AWG OD: 8.5mm			
REFERENCE(参考): UL758 UL1581			
RATING VOLTAGE(电压)V:	3000		
RATING TEMPERATURE(温度)℃:	-60 -200		
CONSTRUCTION(线材结构):			
CONDUCTOR 导体	AWG(线规)	6AWG	
	CONSTRUCTION(结构)	3200/0.08TS+/-0.005mm	
	MATERIAL(材质)	Stranded tinned copper conductor(绞合镀锡铜线)	
	DIA(线径)	5.22mm	
INSULATION(1) 绝缘	MATERIAL(材质)	硅胶	
	AVERAGE THICKNESS(平均厚度)	1.65mm	
	MINIMUM THICKNESS(最薄厚度)	1.55mm	
	DIA(线径)	8.5mm+/-0.1mm	
	COLOR(颜色)	Request according to the customer(根据客户要求)	
INSULATION(2) 绝缘	MATERIAL(材质)		
	AVERAGE THICKNESS(平均厚度)		
	MINIMUM THICKNESS(最薄厚度)		
	DIA(线径)		
	COLOR(颜色)		
MARKING(印字): 6AWG 200℃			
PHYSICAL & ELECTRICAL PROPERTIES(机械物理与电气性能)			
CONDUCTOR RESISTANCE(导体电阻) ohms/km:		1.08Ω/KM	
INSULATION RESISTANCE(承受电流A):		160A	
VOLTAGE WITHSTAND TEST(耐电压) kv/min:		3.0KV	
PREPARED(制作): 刘长风	CHECKED(审核): 汪洋	ISSUE DATE(时间): 2018. 8. 10	